

Ningbo Junsheng Electronics Co.,Ltd.

4.00" (10.00mm)5x7 single color dot matrix Display

Features:

- *Ultra dot intensity
- *Wide viewing angle
- *Range of colors
- *Gray face White segment
- *RoHS compliant

Available option:

- *Alternative face and dot color
- *Cropped terminal pins
- *Available emitting color
- *Low current version

Electro/Optical Characteristics If=20mA Ta=25°C

Part Number Common Cathode	Part Number Common Anode	Emitting Color	Peak Wavelength	Forward Voltage Vf		Luminous Intensity Iv	
				Typ.	Max.	Min.	Typ.
JSD-40571AUR-21	JSD-40571BUR-21	AlGaInP/GaAs Super Red	630	2.00	2.50	20.00	40.00
JSD-40571AUE-21	JSD-40571BUE-21	AlGaInP/GaAs Ultra Red	625	2.00	2.50	80.00	160.00
JSD-40571AUA-21	JSD-40571BUA-21	AlGaInP/GaAs Ultra Amber	605	2.00	2.50	80.00	120.00
JSD-40571AUJ-21	JSD-40571BUY-21	AlGaInP/GaAs Ultra Yellow	590	2.00	2.50	80.00	120.00
JSD-40571AUG-21	JSD-40571BUG-21	AlGaInP/GaAs Yellow Green	574	2.10	2.50	20.00	30.00
JSD-40571APG-21	JSD-40571BPG-21	InGaN/SiC Pure Green	525	3.30	3.80	300.00	400.00
JSD-40571AUB-21	JSD-40571BUB-21	InGaN/SiC Ultra Blue	470	3.30	3.80	80.00	100.00
JSD-40571AUW-21	JSD-40571BUW-21	InGaN/SiC Ultra White	X-0.31/Y-0.31	3.30	3.80	400.00	800.00
Units			nm	V		mcd	

Maximum Ratings Ta=25°C (Derate above 25°C)

Characteristic	Test Condition	Symbol	UR	UE	UA	UY	UG	PG	UB	UW	Units
Pulse Forward Current Per Seg.	1/10 duty cycle 0.1ms Pulse width	I _{FP}	100	100	100	100	100	100	100	100	mA
DC Forward Current Per Seg.		I _F	30	30	30	30	30	30	30	30	mA
Reverse Current Per Seg.	V _R =5V	I _R	10	10	10	10	10	10	10	10	μA
Power Dissipation		P _D	36	40	42	42	44	66	66	66	mW
Operating Temperature		T _{OPR}	-40 to +80								°C
Storage Temperature		T _{TSG}	-40 to +85								°C
Lead soldering temperature	1.60mm from body maximum 3 seconds		260								°C

Checked

Becky Sun

Approved

Jason Lou

Date


Aug/14/2013

PAGE 1 / 2

Ningbo Junsheng Electronics Co.,Ltd.



4.00" (10.00mm) 5x7 single color dot matrix Display

PACKAGE DIMENSION



Tolerance ± 0.25mm unless stated

INTERNAL CIRCUIT DIAGRAM



Checked

Becky Sun

Approved

Jason Lou

Date

Aug/14/2013

PAGE 2 / 2