

Ningbo Junsheng Electronics Co.,LTD.

产品承认书

PRODUCT APPROVED

(CUSTOMERS) _____

(CUSTOMER P/N) _____

(PART NUMBER) JSS-5627A

(DESCRIPTION) 0.56 inch common ca hode 2 digi s smd displa

(SAMPLE DATE) _____

Specification	INSPECTION	SAMPLE	OTHERS
(APPROVED BY)	(CHECKED BY)	(PROOFREAD BY)	(PREPARED BY)

Version	Date	Description	Maker

(CUSTOMER VERDICT)			
(OK)	☐	(NG)	☐

(APPROVED BY):	(APPROVED DATE):
----------------	------------------

(IMPROVED ADVICE):

REMARK: FOR OFFERING THE BEST SERVICE TO CUSTOMER, PLEASE FAX THE DATA TO FACTORY IN TIME


1.DESRIPTION:

- Gra face, White Epoxy
- Common cathode
- Vario s Emi ing ColorColor
- RoHS Complan

2.FEATURES:




- High intensity and reliability
- High quality, Low power requirement
- IC compatible , Easy assembly
- ESD1000V

3.PACKAGE DIMENSION:



NOTES: All dimensions are in millimeters (inches) tolerance are $\pm 0.25\text{mm}$ (0.010) unless otherwise noted

4.INTERNAL CIRCUIT DIAGRAM



5.ABSOLUTE MAXIMUM RATINGS AT T_a=25°C:

Items	Symbol	Absolute maximum Rating	Unit
Forward Current (DC)	IF	20	mA
Power Dissipation	W	60	mW
Peak Forward Current *	IFP	100	mA
Reverse Voltage	VR	5	V
Operation Temperature	T _{opr}	-40+85	°C
Storage Temperature	T _{stg}	-40+100	°C
Lead Soldering Temperature	T _{sol}	Max. 260 °C for 3 sec Max. (3mm from the base of the epoxide lb)	


6.ELECTRICAL/OPTICAL CHARACTERISTICS AT T_a=25°C:

Part No	Emitting Color	Chip Material	Forward Voltage (V)		Luminous Intensity (mcd)		Peak Wavelength (nm)	
			IF=10mA					
Common Cathode			T _p	Max	Min	T _p	T _p	Max
JSS-5627AUR-21	Ultra Red	AlGaInP	2.0	2.5	20	40	630	640
JSS-5627ASR-21	Super Red	AlGaInP	2.0	2.5	40	80	620	625
JSS-5627AUY-21	Yellow	AlGaInP	2.0	2.5	40	60	585	595
JSS-5627AUG-21	Green	AlGaInP	2.0	2.5	10	20	570	575
JSS-5627AUA-21	Amber	AlGaInP	2.0	2.5	40	60	600	610
JSS-5627AUB-21	Blue	InGaN	3.0	3.5	40	60	460	470
JSS-5627APG-21	Pure Green	InGaN	3.0	3.5	80	150	520	525
JSS-5627AUW-21	White	InGaN	3.0	3.5	100	200	X0.30/Y0.30	

7.Recommended Soldering Pattern:




8、推荐的 SMT 焊接曲线 Recommended SMT condition:




NOTES:

- 1.We recommend the reflow temperature 245°C (+/-5°C). The maximum soldering temperature should be limited to 260°C.
- 2.Don't cause stress to the epoxy resin while it is exposed to high temperature.
- 3.Number of reflow process shall be 2 times or less.

9.Reel Dimensions:



10.Packing and Lable Specifications:



Note: The specifications are subject to change without notice. Please contact us for updated information.